


Specs. for Tape Samples
 Fiberglass PET Tape

Art. 1618-30GB

Adhesive: Rubber
B Class-130°C (B)

Fiberglass Enhanced Polyester Adhesive Tape

This tape is made by material of fiberglass and polyester with high strength good adhesive mechanical properties. It can withstand moisture environment and friction. It has chemical property of solvent-resistance. It is widely used on binding and fixing for coil.



UL

Adhesive: Rubber, Specifications: B Class-130°C (B)

Model:	1618-30GB
BACKING TYPE	Polyester film and glass fibre
ADHESIVE TYPE	Rubber
COLOR	Transparent
BACKING THICKNESS	0.1 mm
TOTAL THICKNESS	0.18 mm
ADHESIVENESS TO STEEL (N/CM)	≥10 N/cm
TENSILE STRENGTH	≥240 N/cm
ELONGATION AT BREAK	≥6%
BREAKDOWN VOLTAGE	≥ 5 kV
THERMAL CLASS	130 (B)
ELECTROLITIC CORROSION	1
SHELF LIFE	12 months
STANDARD LENGTH	50 m

Storage Notes:

1. Store sealed in room temperature 15°C~25°C, relative humidity 50%(±30%) , avoid moisture and direct sunlight.
2. After 1 year storage at room temperature, the main indexes did not decrease obviously. When long-term storage exceeds 1 year, users are advised to test before using it.